

# Mitchell

## TD400

...It's **ELECTRIC!**

The Mitchell TD400 guitars (Traditional Double-Cutaway) offer an alder body with an off-set double-cutaway design, and a versatile and familiar H/S/S pickup system that provides the look and tone that rock and blues musicians search for — at home, in studios and on weekend stages.

### BASICS

- Alder body, off-set double-cutaway design
- One-piece maple neck with rosewood stripe
- Custom H/S/S pickup configuration

### FEATURES AND BENEFITS

- Pull coil-tap humbucker for single-coil sounds
- Locking tuners and Graph Tech™ TUSQ XL reduced-friction nut enhance tuning stability
- Wilkinson VS50-II with locking saddles and heavy bridge block adds tone and sustain
- High-tensile strength fretwire provides durability and smooth playability



### HIGHLIGHTS



Paraffin-dipped pickups reduce microphonics & feedback



Ultra-carve heel joint allows comfortable access to upper frets



Slim-taper neck feels great in any player's hands



Staggered height tuners keep the right amount of string tension at the nut

### TD400 SERIES SPECIFICATIONS

BODY STYLE	Traditional Double-Cutaway
BODY MATERIAL	Alder
BODY BINDING	N/A
TUNERS	18:1 Die-Cast Locking, Staggered Height
NUT	TUSQ XL™
PICKUP CONFIGURATION	SSH
Neck Pickup	Single Alnico V
Middle Pickup	Single Alnico V
Bridge Pickup	Humbucker Alnico V
CONTROLS	Master Volume, Master Tone
SWITCHING	5-Way Blade Switch
COIL TAP	Pull Tone Pot (Humbucker only)
BRIDGE	Wilkinson™ VS50-II Tremolo
HARDWARE	Nickel
PICKGUARD	White Pearlloid
AVAILABLE FINISHES	Black (BK), Sunburst (SB)

NECK STYLE	Bolt-On
NECK SHAPE	Shallow "D"
NECK MATERIAL	Rock Maple w/Rosewood Center Stripe
NECK FINISH	Tung Oil
NECK BINDING	N/A
# OF FRETS	22
FRETWIRE	Jumbo
SCALE LENGTH	25.5" (648mm)
RADIUS	240mm (9.5")
WIDTH AT NUT	43mm (1.7")
WIDTH AT LAST FRET	57mm
THICKNESS AT 1ST FRET	20mm
THICKNESS AT 12TH FRET	22mm
FRETBOARD	Indian Rosewood
INLAY	Offset Abalone Dot
TRUSS ROD	2-Way Adjustable (4mm Hex Wrench)